

## PoolBasic LED

PoolBasic LED is a user-friendly **analogue combined system with a peristaltic dosing pump and single measurement with automatic proportional dosing** that enables chemical adjustment for above ground pools.

### POOLBASIC LED

- for pH (6.2 – 8.2)
- for ORP (480 – 750 mV / 660 – 930 mV)

### PROPORTIONAL DOSING PUMP

Flow rate 1.5 or 5 l/h ; Pressure 1.5 bar

**POOL SIZE** Indoor 5 – 130 m<sup>3</sup> ; Outdoor 5 – 110 m<sup>3</sup>

### MAIN BOARD

Display LED

Power supply 220 – 240 Vac 50/60Hz

### IP65 ENCLOSURE

Dimensions 234 x 162 x 108 mm

Material PP



## PoolBasic Plus

PoolBasic Plus delivers a user-friendly solution combining a **peristaltic dosing pump and single measurement with automatic proportional dosing** that adjusts the chemical parameters for above ground pools.

### POOLBASIC PLUS

- for pH (0 – 14)
- for ORP (0 – 1000 mV)
- for ORP with shuko (0 – 1000 mV)

### PROPORTIONAL DOSING PUMP

Flow rate 1.5 or 5 l/h ; Pressure 1.5 bar

**POOL SIZE** Indoor 1 – 130 m<sup>3</sup> ; Outdoor 1 – 110 m<sup>3</sup>

### MAIN BOARD

Alphanumeric display 16 letters x 2 lines

Power supply 220 Vac 50/60Hz

### IP65 ENCLOSURE

Dimensions 234 x 162 x 108 mm

Material PP

